



NOTES:

- 1) MATERIAL: AISI 304/316 STAINLESS STEEL SHEET ANNEALED 2B FINISH, 16 GAUGE (0.063 THICK)  
PER AMS 5513 (304) OR 5524 (316) OR ASTM A240 OR ASME SA240  
REF DART SPEC. M304S16GA
- 2) FINISH: PRIME IAW MIL-P-23377J TYPE I CLASS N; 1-2 MIL MAX, AS PER QSI 005.
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D4976-1", AGUSTA WESTLAND P/N "TBD", REVISION, BATCH NUMBER AND DATE OF MANUFACTURE,  
USING AN X-TENSION STAMP, PER QSI 044 METHOD 6.2
- 7) WEIGHT: 0.05 lbs (0.02 kgs)
- 8) UNDIMENSIONED FEATURES CONTROLLED BY CAD MODEL FILE: D4976-1-a.IGES

APPROVED

A	NEW ISSUE	DC	13.11.12
REV.	DESCRIPTION		BY DATE
DESIGN	DC	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA	
DRAWN	DC		
CHECKED	RF	DRAWING NO.	REV. A
MFG. APPR.	JLM	<b>D4976</b>	SHEET 1 OF 1
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	<b>BRACKET</b>	NTS
DATE	13.11.28		<p><b>COPYRIGHT © 2013 BY DART AEROSPACE LTD</b> THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</p>